



Assembly Instructions

Traditional Bench



*Thank you for choosing **A&L Furniture Co.***

We hope that this piece brings you many years of enjoyment!

For help with assembling your furniture,
or if you have missing hardware, please email us at
help@aandlfurniture.com or call us at 866-896-5747

PARTS (included)

(A) Bench Top (1)



(B) Bench Legs (2)



(C) Leg Braces (2)



HARDWARE

(a) 2³/₄" Bolts (4)

(b) 2¹/₂" Lag Screws (4)

(c) Allen Wrench (1)



TOOLS NEEDED

Hammer for light tapping

⁷/₁₆" Wrench or Socket

STEP 1

Lay bench top upside down on a clean flat surface. Attach bench legs to the inside of the 2x2's (see photo 1). Align the predrilled holes on the bench legs with the threaded inserts in the 2x2. (Note: If the holes in the legs do not align with the inserts, the legs can be adjusted with your hands by pushing or pulling at the top of the legs.) Now insert 2³/₄" bolts through the leg and turn into the inserts (see photo 2). Tighten with the Allen wrench. Be sure horizontal brace on leg is turned toward the end of the bench.




photo 1




photo 2

STEP 2

Attach the braces to the bench by placing one end of the brace on the bench top (be sure to stay to one side of the crack between the boards) and the other end against horizontal brace on legs (see photo 3). Insert 2¹/₂" lag screw into the predrilled holes in the braces (see photo 4). Tap with hammer to get them started then tighten with ⁷/₁₆" wrench or socket. The lags are self drilling and will not crack the wood. (Do not over tighten as this may cause them to break.) If the bench rocks or seems unstable loosen bolts. Set bench upright on floor and put some weight on it before tightening bolts again.




photo 3




photo 4